Amendments to the Specification:

Please amend the **Description of the Drawings** as follows:

Figure 1 is a photograph showing a perspective view of the assembled coupler lock of <u>an</u> <u>embodiment of</u> the present invention showing the shaft inserted into the lock body of the coupler lock and a key inserted into the keyway of the coupler lock;

Figure 2 is shows an exploded view of the coupler lock of Figure 1 the present invention;

Figure 3 is a drawing of a side view of the coupler lock of Figure 1 the present invention showing the shaft inserted into the lock body of the coupler lock[[.]];

Figure 4A is a side view of the coupler lock of Figure 1[[.]];

Figure 4B is a cross-sectional view of the coupler lock <u>of Figure 1</u> as taken through A-A as shown in Figure 4A[[.]];

Figure 4C is a cross-sectional view of the coupler lock of Figure 1 as taken through B-B as shown in Figure 4A[[.]];

Figure 4D is an end view of the coupler lock of Figure 1[[.]];

Figure 4E is a cross-sectional view of the coupler lock of Figure 1 as taken through C-C as shown in Figure 4D[[.]];

Figure 5 is a <u>perspective view</u> drawing of the neck of a trailer, showing a latch in a closed position and a coupler lock attached to the latch such that the latch cannot be placed in an open position without removal of the coupler lock[[.]];

Figure 6 is a <u>perspective view drawing</u> of the neck of another trailer, showing a latch in a closed position and a coupler lock attached to the latch such that the latch cannot be placed in an open position without removal of the coupler lock[[.]];

Figure 7A is an exploded view of a second embodiment of the present invention[[.]]; and

Figure 7B is a perspective view of the embodiment shown in Figure 7A.